

# Product data sheet

LUCAS I (WALL FITTING)  
9.835.5507.15  
LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



2 x Compact fluorescent lamp			
Nominal lamp power	26 W	LOR	84%
Lamp flux	1800 lm	Total flux	3016 lm
Luminous efficacy	54 lm/W	Total power	56 W
CCT	2899 K		
CRI	90		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 22.44 in

Diameter: 22.44 in

## Design

Material impression: Matt

Color of housing: White

## Electric

System power: 56 W

Ballast: ECG

Controller: DALI

## Protection

IP: 55

Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...95°F