Product data sheet

SINTESI INFINITY - SUSPENSION-CEILING - TO BE COMPLETED WITH ROLL DIFFUSER 4000K CRI 80 29W CLD BLACK + PR 22011731-0072+22025844-33

DISANO



Housing: in extruded aluminium. Diffuser: opal polycarbonate (to be purchased separately). : UGR<lt/>19 IF COMPLETE WITH PRISMATIC ROLL DIFFUSER 22025844-33 Coating: epoxy polyester powder coating resistant to UV rays. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: supplied standard, versions complete with mounting brackets for installation as pendant lamps (suspensions to be purchased separately) and as ceiling fixtures. On request: • emergency wiring CLD E with sub-code -09. • emergency wiring with centralized power supply CLD EC with sub-code -0050. • CLD D-D (DALI) wiring with sub-code -1241. • white colour.

Light output 1



1 x LED

Nominal lamp power	29 W	LOR	100%
Lamp flux	3500 lm	Total flux	3500 lm
Luminous efficacy	121 lm/W	Total power	29 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 110.31 in
Width: 2.52 in
Height: 2.91 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 29 W
Appliance Class: I

Protection

IP: 00
IK: 07
Designation labels: CE