Product data sheet

DECORATIVE LIGHTING

V1-R0-9T502-30D01-2003040 COSMO T 600X544 SUSPENDED 30W 4000K DALI


VARTON



IP 40 IK 03

• Triangle luminaire with homogenous illumination and smooth angles. • Material: Stainless steel housing Application • Offices • Corridors • Lobbies • Reception areas • Hospitality (restaurants, hotels, coffee bars) Installation • Suspended Input voltage (AC, 50Hz), V: 220...240 AC frequency, Hz: 50 Flicker, %: 5 Climatic modification and category of placement: УХЛ4 Protection class: I Housing material: Aluminium Mounting method: Pendant Ingress protection (IP): IP40 Impact resistance: IK03 Power factor: 0,95 https://www.varton.ru/products/interernoe-dekorativnoe-osveshchenie/cosmo-t/cosmo-t-600x544-podvesnye/svetodiodnyy-svetilnik-varton-cosmo-t-600kh544kh115-mm-30-vt-podvesnoy-cri90-4000-k-ral9005-chernyy-/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	73 lm/W	Total power	30 W
CCT	4000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Length: 23.62 in
Width: 21.42 in
Height: 4.53 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 40
IK: 03