

Product data sheet

KIT LED BETA 430 - L1551- 2X65W AMPIO


A5308

3F FILIPPI



Beta 430 Retrofit Kit to replace the 4x49W T5 Amalgam or the 4x58W T8 version ILLUMINOTECHNICAL Luminous efficiency 100% (DLOR 100%, ULOR 0%). Initial luminous flux of the luminaire 19205 lm. Wide symmetric distribution. Installation Interdistance Transv.D = 1.49 x hu - Long.D = 1.54 x hu. Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 19.3 - 19.8. Beam angle: 100° - 100°. Luminous efficacy 160 lm/W. Lifetime (L93/B10): 30000 h. (tq+25°C) Lifetime (L90/B10): 50000 h. (tq+25°C) Lifetime (L85/B10): 80000 h. (tq+25°C) Lifetime (L80/B10): 100000 h. (tq+25°C) Lifetime (L85/B10): 50000 h. (tq+40°C) Sudden decreased luminous flux after 50000 hours: 0% (C0). Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471). In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards. SOURCE 2 linear LED modules 65W/840. Energy efficiency class (UE 2019/2020 - UE 2019/2015): C. CIE 13.3 Colour rendering index: CRI >80 (R9 <50%). IES TM-30 Fidelity Index: Rf = 84 Rg = 95. CCT nominal colour temperature 4000 K. Colour initial tolerance (MacAdam): SDCM 3. MECHANICAL Gear-tray unit hot-galvanised steel, painted in white polyester. Methacrylate (PMMA) lenses with external flat surface. Luminaire with limited surface temperature. - D - (EN 60598-2-24) Dimensions: 1551x430 mm, height 159 mm. Weight 5.417 kg. Glow-wire test resistance 850°C. ELECTRICAL Halogen Free electronic wiring 230V-50/60Hz, power factor 0.97, THD <25%, constant output current, class I, 2 driver. Twin-circuit. Power of the luminaire 120 W. CE - IEC 60598-1 - EN 60598-1. SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC. Ambient temperature from -20°C to +40°C. Temperature class T6 max 85°C. Relative humidity UR: <85%. INSTALLATION Retrofit. Correct installation of the retrofit LED kit, compliant with EN 60598-1 and CE marked, inside the 3F Filippi - Beta 4x and 6x i3F 76 Fluorescent luminaires must be only carried out by qualified personnel to ensure compliance with the national installation standards. Attention: to maintain the degree of protection of the device and for the purposes of validity of the guarantee of the new retrofit kits, it is imperative to replace the old cable guides (on the body of the device) with the new ones supplied. All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com. WARNING Fixture not suitable for cold stores with an ambient temperature <0°C and/or relative humidity >85%. Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	120 W	CRI	80
Total flux	19205 lm	LOR	100%
Luminous efficacy	160 lm/W	Total power	120 W

Mounting mode

Ceiling mounted

Electric

System power: 120 W

Appliance Class: I

Shape and measurements

Length: 61.06 in

Width: 16.93 in

Height: 6.26 in

Adjustability

Fixed

Design

Color of housing: White