Product data sheet

VOLKMAR III (2-ARMED) 9.870.0204.00

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately - Order pole for multi-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1




1 x High pressure mercury vapour lamp			
Nominal lamp power	50 W		
Lamp flux	2000 lm		
Luminous efficacy	19 lm/W		
CCT	3400 K		
CRI	54		

LOR	55%
ULOR	15%
Total flux	1092 lm
Total power	59 W




1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR			
Lamp flux	4000 lm	ULOR			
Luminous efficacy	25 lm/W	Total flux			
CCT	3400 K	Total power			
CRI	54				

Light output 2



1 x High pressure mercury vapour lamp				
Nominal lamp power	50 W	LOR	55%	
Lamp flux	2000 lm	ULOR	15%	
Luminous efficacy	19 lm/W	Total flux	1092 lm	
CCT	3400 K	Total power	59 W	
CBI	54			

55% 15% 2185 lm 89 W



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	55%
Lamp flux	4000 lm	ULOR	15%
Luminous efficacy	25 lm/W	Total flux	2185 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted, Ceiling mounted

Shape and measurements

Height: 28.35 in Diameter: 16.14 in

Design

Material impression: Matt Color of housing: White

Electric

System power: 118-178 W

Ballast: ECG

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 55

Designation labels: CE, ENEC, F

Other operating numbers

Ambient temperature range: -4...95°F