


Product data sheet

LINA60-S 04S-200F-20GGE/940, B
04S-200F-20GGE/940
HALLA




04S-200F-20GGE/940, B Luminaire recessed/surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 561 x 57 x 67 mm Type of installation: Recessed, Surface, Suspended Distribution: Direct Optics type: Reflector Protection class: I Voltage: 220-240V

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 20 W | CRI | 80 |
| Total flux | 1750 lm | LOR | 100% |
| Luminous efficacy | 88 lm/W | Total power | 20 W |

Light output 2 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 20 W | CRI | 80 |
| Total flux | 1750 lm | LOR | 100% |
| Luminous efficacy | 88 lm/W | Total power | 20 W |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 6.30 in
Diameter: 2.17 in

Adjustability

Rotatable, Tilttable

Electric

System power: 40 W
Appliance Class: I

Protection

IP: 20