

Product data sheet


RICHARD II (2-ARMED)
9.893.1032.00
LEIPZIGER LEUCHTEN



IP
55


Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 60 mm, separately Order pole for double-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| | | | |
|-----------------------|---------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 70 W | LOR | 43% |
| Lamp flux | 7200 lm | ULOR | 8% |
| Luminous efficacy | 35 lm/W | Total flux | 3094 lm |
| CCT | 3000 K | Total power | 89 W |
| CRI | 90 | | |

Light output 2



| | | | |
|-----------------------|---------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 70 W | LOR | 43% |
| Lamp flux | 7200 lm | ULOR | 8% |
| Luminous efficacy | 35 lm/W | Total flux | 3094 lm |
| CCT | 3000 K | Total power | 89 W |
| CRI | 90 | | |

Mounting mode

Pole top mounted

Electric

System power: 178 W

Shape and measurements

Height: 24.21 in

Diameter: 9.84 in

Protection

IP: 55