


Product data sheet

PURE3 HEXAGON SURFACE WHITE SAT.

P33A15H-9016C1930L3S


PLANLICHT



IP
20


LED LO 3000K 58W 5730lm DALI CRI90 <https://katalog.planlicht.com/en-us/fam-pure3/>

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	955 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	23%
		Total power	9.65 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	955 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	23%
		Total power	9.65 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	955 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	23%
		Total power	9.65 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	955 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	23%
		Total power	9.65 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	955 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	23%
		Total power	9.65 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.65 W	CRI	90
Total flux	955 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	23%
		Total power	9.65 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 59.45 in

Width: 51.50 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 57.9 W

Protection

IP: 20