


Product data sheet

KIPP WALL, LED 28W / 3000K
5743400768
LOUIS POULSEN



Kipp Wall Design : Alfred Homann Light concept : The fixture emits symmetrical light directed downward. The relation between the slightly curved top shade and the angle of the inner opal diffuser ensures a wide non glare light distribution. Finish: Aluminium coloured with textured surface or graphite grey, powder coated. Material: Diffuser: Injection moulded white opal acrylic. Top shade: Die cast aluminium. Enclosure: Injection moulded clear polycarbonate. Frame: Die cast aluminium. Wall box: Die cast aluminium. Arm: Extruded aluminium. Mounting: Terminal block: 1x3x2.5mm². Cable entries: 2x rear and 2x bottom entries, Ø 20mm. Looping: Approved, max. 3x1,5mm². Weight: Max. 7,5 kg Class: Ingress protection IP55. Electric shock protection I w. ground. Vandal Proof II.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	1454 lm	LOR	100%
Luminous efficacy	52 lm/W	ULOR	10%
		Total power	28 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 79.13 in

Diameter: 17.32 in

Adjustability

Fixed

Electric

System power: 28 W

Appliance Class: II

Protection

IP: 55

IK: 10