


# Product data sheet

VIGILANT LED HIGH BAY 13500 LUMENS, WIDE DISTRIBUTION, DIFFUSED POLYCARBONATE LENS  
HEX5WC2BXXXXXN  
DIALIGHT



Vigilant LED High Bay 13,500 Lumens 102 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Diffused Polycarbonate Lens UL 1598/A (wet locations) CSA C22.2 No. 250 NEMA 4X CE, ENEC EN 60598-1:2015 EN 60598-2-1 (ed. 1), IEC 60598-2-1 (ed. 8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2015 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-24 IK10 Wide Distribution IP66/67 Scaled IES File

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 5181 K |
| Nominal lamp power | 102 W    | CRI         | 80     |
| Total flux         | 13499 lm | LOR         | 100%   |
| Luminous efficacy  | 132 lm/W | Total power | 102 W  |

## Mounting mode

Pendant

## Shape and measurements

Height: 3.00 in

Diameter: 15.96 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 102 W

Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC

Appliance Class: I

## Protection

IP: 66

IK: 10