# Product data sheet


TRIONA RECTANGLE P
312728.002.730
RZB



IP 20 IK 03

Series: TRIONA rectangle Decorative rectangular LED pendant area luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Canopy made of aluminium, powder-coated. Direct light emission through a diffuser made of non-yellowing plastic (PMMA) microprismatic.Indirect light emission through a flush diffuser made of satin-finish plastic. LED backlight technology for homogeneous illumination of the entire light-emitting surface. Direct 60%, indirect 40% light emission. 2-point steel cable suspension, steplessly adjustable. Easy installation with transparent, adjustable pendant cable and canopy with magnetic fixing. Driver integrated. With Casambi smart+free Bluetooth control for wireless network and operation using Android / iOS devices, free app available for download. Direct/indirect light emission can be switched and controlled separately. Suitable for through-wiring. Colour: traffic white, matt (RAL 9016) Length: 1300 mm Width: 350 mm Height: 52 mm Suspension length: 500-1200 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 Light source: LED Socket lamp2: Without base Colour temperature: 3000K System power: 96 W Rated luminous flux: 11600 lm Beam angle Down: 93° / 95° Luminous efficiency: 121 lm/W Control gear: Dimmable Bluetooth converter Control gear: Konverter dimmbar Bluetooth Protection class: I Type of protection: IP 20

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 96 W | CRI | 80 |
| Total flux | 11600 lm | LOR | 67% |
| Luminous efficacy | 121 lm/W | ULOR | 14% |
| | | Total power | 96 W |

### Mounting mode

Pendant

### Shape and measurements

Length: 13.78 in
Width: 51.18 in
Height: 2.05 in

### Adjustability

Fixed

### Design

Color of housing: White

### Electric

System power: 96 W

### Protection

IP: 20
IK: 03