

# Product data sheet

LUNOVA 830 CLO DALI CL2  
303637-461  
FAGERHULT



IP  
66

Installation Luminaire for assembly on a post, with post top Ø 60 mm or Ø 76 mm. Connection Supplied with 6 m connection cable (H05RN-F). Design Body and heat sink of cast aluminium with stainless steel details. Diffuser of impact and UV-resistant acrylic. Ballast integrated in the luminaire. Reflector Pressure-turned white-enamelled aluminium reflector. Dimming Available with a number of different light regulation options. Miscellaneous Projected wind shield 0,086m². Designed by White Design - Torbjörn Eliasson and Andreas Sture. Standard Colour Anthracite grey (Gris 900 Sablé). Other colours with additional number: Alugrey (RAL 9006) -236. Black (RAL 9005) -230. White (RAL 9010) - 311.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	2000 lm	LOR	100%
Luminous efficacy	71 lm/W	ULOR	7%
		Total power	28 W

## Mounting mode

Pole top mounted

## Electric

System power: 28 W

## Shape and measurements

Length: 21.75 in  
Width: 21.75 in  
Height: 10.97 in

## Protection

IP: 66

## Adjustability

Fixed

## Design

Color of housing: Black, Silver gray, White