
Product data sheet


LINEDO_2,3M_90_1111
952390.843.5M1.024
RZB



IP 54 IK 03


LINEDO, 50. 109 W, 10200. 20800 lm, 840, black, on/off Continuous line luminaire, L 2291 B 58 H 76

Light output 1




1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	4100 lm	Total flux	4100 lm
Luminous efficacy	195 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	27.3 W	LOR	100%
Lamp flux	5200 lm	Total flux	5200 lm
Luminous efficacy	190 lm/W	Total power	27.3 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	12.5 W	LOR	100%
Lamp flux	2550 lm	Total flux	2550 lm
Luminous efficacy	204 lm/W	Total power	12.5 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	17.3 W	LOR	100%
Lamp flux	3450 lm	Total flux	3450 lm
Luminous efficacy	199 lm/W	Total power	17.3 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	14.5 W	LOR	100%
Lamp flux	2950 lm	Total flux	2950 lm
Luminous efficacy	203 lm/W	Total power	14.5 W
CCT	4000 K		
CRI	80		

Light output 2




1 x LED

Nominal lamp power	12.5 W	LOR	100%
Lamp flux	2550 lm	Total flux	2550 lm
Luminous efficacy	204 lm/W	Total power	12.5 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	27.3 W	LOR	100%
Lamp flux	5200 lm	Total flux	5200 lm
Luminous efficacy	190 lm/W	Total power	27.3 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	4100 lm	Total flux	4100 lm
Luminous efficacy	195 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	17.3 W	LOR	100%
Lamp flux	3450 lm	Total flux	3450 lm
Luminous efficacy	199 lm/W	Total power	17.3 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	14.5 W	LOR	100%
Lamp flux	2950 lm	Total flux	2950 lm
Luminous efficacy	203 lm/W	Total power	14.5 W
CCT	4000 K		
CRI	80		

Light output 3




1 x LED

Nominal lamp power	12.5 W	LOR	100%
Lamp flux	2550 lm	Total flux	2550 lm
Luminous efficacy	204 lm/W	Total power	12.5 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	14.5 W	LOR	100%
Lamp flux	2950 lm	Total flux	2950 lm
Luminous efficacy	203 lm/W	Total power	14.5 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	27.3 W	LOR	100%
Lamp flux	5200 lm	Total flux	5200 lm
Luminous efficacy	190 lm/W	Total power	27.3 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	21 W	LOR	100%
Lamp flux	4100 lm	Total flux	4100 lm
Luminous efficacy	195 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	17.3 W	LOR	100%
Lamp flux	3450 lm	Total flux	3450 lm
Luminous efficacy	199 lm/W	Total power	17.3 W
CCT	4000 K		
CRI	80		

Light output 4




1 x LED

Nominal lamp power	27.3 W	LOR	100%
Lamp flux	5200 lm	Total flux	5200 lm
Luminous efficacy	190 lm/W	Total power	27.3 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	4100 lm	Total flux	4100 lm
Luminous efficacy	195 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	17.3 W	LOR	100%
Lamp flux	3450 lm	Total flux	3450 lm
Luminous efficacy	199 lm/W	Total power	17.3 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	14.5 W	LOR	100%
Lamp flux	2950 lm	Total flux	2950 lm
Luminous efficacy	203 lm/W	Total power	14.5 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	12.5 W	LOR	100%
Lamp flux	2550 lm	Total flux	2550 lm
Luminous efficacy	204 lm/W	Total power	12.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 90.20 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 50-109.2 W

Protection

IP: 54
IK: 03