
Product data sheet


HALO CENTRALIZED SUSPENSION WHITE 1220MM
R48Z122-9016C1930L1S
PLANLICHT



IP 20


LED LO 3000K 40W 3118lm https://katalog.planlicht.com/en-us/fam-halo/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	5 W

Mounting mode

Pendant

Shape and measurements

Length: 48.03 in
Width: 48.03 in
Height: 2.17 in

Adjustability

Fixed

Electric

System power: 40 W

Protection

IP: 20
Designation labels: CE