Product data sheet

ASL 70 DA LED (OPTIC 028)
9.104.8114.06028-3
LEIPZIGER LEUCHTEN



IP 65

• recommended pole height 4.00m - 8.00m • cap made of plastics, impact resistant and glass fibre reinforced – removable and captive; carrying housing made of corrosion resistant cast aluminium with inner white special paint; dyed and powder coated • glazing made high-quality acrylic, clear, partly textured, with stainless steel fastener • completely wired; via a clamp within the luminaire head • for side entry ø 42mm up to ø 48mm; with adapters AS 60 for top entry ø 60mm or AS 76 for top entry ø 76mm • to be ordered separately: adapter AS 76 for post top ø 76mm, adapter AS 60 for post top ø 60mm, pole, pole accessories, wall bracket, cable, for DA LED: back light shield for non- glare on the rear side

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11 W	CRI	70
Total flux	1557 lm	LOR	84%
Luminous efficacy	142 lm/W	Total power	11 W

Mounting mode

Pole integrated

Shape and measurements

Length: 17.91 in
Width: 9.37 in
Height: 8.27 in
Weight: 6.8 kg

Adjustability

Height adjustable

Electric

System power: 11 W

Protection

IP: 65