Product data sheet


QBA 1 70W 230V HST-DE A/S
96012205
THORN LIGHTING



IP 66 IK 08

A compact discharge floodlight for architectural lighting with IP66 optical and gear compartment, SC1 class. Grey powder coated die-cast aluminium body with Flat Glass enclosure. Projector is fully adjustable on a short stirrup, locked via central 8mm diameter allen screws. asymmetrical floodlighting distribution with a aluminium - texturebrite reflector. This product is suitable for a 70 W HST-DE lamp. Available in other colours as special (any RAL number, brick brown or pale sand). Dimensions: 227 x 188 x 212 mm Weight: 4.6 kg

Light output 1



1 x General service incandescent lamp

Nominal lamp power	70 W	LOR	57%
Lamp flux	6800 lm	Total flux	3904 lm
Luminous efficacy	46 lm/W	Total power	84 W
CCT	3000 K		
CRI	99		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 8.94 in
Width: 7.40 in
Height: 8.35 in
Weight: 4.6 kg

Design

Material impression: Aluminum

Electric

System power: 84 W
Voltage: 230-240 V AC
Appliance Class: I

Protection

IP: 66
IK: 08
Designation labels: CE