


Product data sheet

EDGE GRAPHITE 580LM 3000K RA>80 TRAILING EDGE DIMMING
7021986233513
SG ARMATUREN



Attractive, square wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a down/uplight or as a down or uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK06. Light distribution Direct/Indirect Light technic LED 7W 3000K Ra>80 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP65 IK06 Materials and finish Housing: Aluminium Colour: Graphite Optics: Tempered glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



1 x LED			
Nominal lamp power	7 W	LOR	100%
Lamp flux	580 lm	ULOR	49%
Luminous efficacy	83 lm/W	Total flux	580 lm
CCT	3000 K	Total power	7 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 12.60 in
Width: 4.06 in
Height: 2.36 in

Adjustability

Fixed

Electric

System power: 7 W
Appliance Class: I

Protection

IP: 65
IK: 06