


Product data sheet

CIRCULAR OUTWARD 2 RINGS (Ø900 Ø600)
CF4N-00W9AZRU14
LEDSC4




LedsC4 Circular Outward 2 Rings (Ø900 Ø600) CF4N-00W9AZRU14V1 Pendant for indoor use. For sideways lighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 9 Product width or diameter (mm): 884 Product height (mm): 6500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 86W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 6172. Real lm/W: 68. Voltage / frequency range: 100-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 91. Power factor: 0.90. Dimmable equipment included: 0-10V.

Light output 1



1 x LED			
Nominal lamp power	52.5 W	LOR	100%
Lamp flux	2770 lm	ULOR	49%
Luminous efficacy	53 lm/W	Total flux	2770 lm
CCT	3000 K	Total power	52.5 W
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	38.5 W	LOR	100%
Lamp flux	3402 lm	ULOR	50%
Luminous efficacy	88 lm/W	Total flux	3403 lm
CCT	3000 K	Total power	38.5 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 35.43 in
Width: 35.43 in
Height: 1.18 in

Electric

System power: 91 W
Appliance Class: I

Protection

IP: 20

Adjustability

Fixed