


# Product data sheet

FELIX IV  
9.899.1032.04  
LEIPZIGER LEUCHTEN



Three optional reflector panels may be (alternately) fitted at symmetrical/asymmetrical angles to give a wide variety of lighting arrangements. Recommended mounting height 4.50 m - Attachment made of thermal protective glass - Variety of radiation effects with large aluminium reflector and panels which may be arranged at different positions - Reflector surface finished in white paint - Luminaire body made of high-quality cast aluminium, outside painted in color - Luminaire wired ready for connection - Available in any RAL or DB color without surcharge - Twin tube pole with pedestal, hot galvanized and painted is included in scope of supplies.

## Light output 1



|                              |         |             |         |
|------------------------------|---------|-------------|---------|
| <b>1 x Metal halide lamp</b> |         |             |         |
| Nominal lamp power           | 70 W    | LOR         | 77%     |
| Lamp flux                    | 7400 lm | ULOR        | 29%     |
| Luminous efficacy            | 63 lm/W | Total flux  | 5723 lm |
| CCT                          | 3000 K  | Total power | 91 W    |
| CRI                          | 90      |             |         |

## Mounting mode

Pole top mounted

## Electric

System power: 91 W

## Shape and measurements

Length: 7.87 in

Width: 7.87 in

Height: 11.81 in