



# Product data sheet

1513 TORCIA LED COB 3000K CRI 80 60.4W CLD GRAPHITE  
423251-39  
DISANO



Housing: in die-cast aluminium. Attachment: suited for poles with a diameter of 60 mm. Diffuser: in polycarbonate, transparent, anti-glare, shatterproof and V2 self-extinguishing, UV stabilised. Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Special coating: upon request: available with coating tested to withstand corrosion tests in aggressive artificial atmospheres (UNI EN ISO 9227) or marine environments (sea front). Heat Sink: built-in. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - IP67 quick connector. - anti-condensation valve. - temperature controller with auto-reset. - EN 61547 compliant surge protection. Mounting: on 60 mm diameter pole or bracket.

## Light output 1



1 x cob-1513_3k			
Nominal lamp power	60.4 W	LOR	100%
Lamp flux	4706 lm	ULOR	10%
Luminous efficacy	78 lm/W	Total flux	4706 lm
CCT	3000 K	Total power	60.4 W
CRI	80		

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 21.18 in  
Width: 20.98 in  
Height: 30.12 in

## Adjustability

Fixed

## Design

Material impression: Aluminum  
Color of housing: Anthracite / graphite

## Electric

System power: 60.4 W  
Appliance Class: II

## Protection

IP: 66  
IK: 08  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...104°F