
# Product data sheet

INDIVIDUAL BATTEN LUMINAIRE BOARD 2 M1200 26W 3350LM CRI > 2009.6203 - BOARD2 SM M1200 LED3350-830 DIR WH DALI


REGENT



IP 40 IK 08

Individual batten luminaire Board 2 m1200, with LED, system power: 26 W, standby power 0.5 W, luminous flux of luminaire 3350 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, housing in aluminium, white, RAL 9016, diffuser in polycarbonate (PC) opal, 1 integral control gear, DALI2, protection class I, ingress protection IP40, glow wire test 850 °C, impact strength: IK 08, for ambient temperatures -20 to +35 °C, this product contains a light source of energy efficiency class D and EPREL registration number: 777637 L = 1150 mm, B = 51 mm, H = 73 mm

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 26.4 W | LOR | 100% |
| Lamp flux | 3350 lm | ULOR | 14% |
| Luminous efficacy | 127 lm/W | Total flux | 3350 lm |
| CCT | 3000 K | Total power | 26 W |
| CRI | 80 | | |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 45.35 in
Width: 1.93 in
Height: 2.76 in
Weight: 1.4 kg

### Adjustability

Fixed

### Design

Color of housing: White

### Electric

System power: 26 W
Appliance Class: I

### Protection

IP: 40
IK: 08