

Product data sheet

GANDALF 25 STREET AND AREA LIGHTING LUMINAIRES

GA-90254-W-W40

LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light outputs 1..2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	75.3 W	CRI	80
Total flux	7699 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	75.3 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 47.56 in
Width: 12.60 in
Height: 4.72 in
Weight: 17.5 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 150.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C