


# Product data sheet

SCOOT 450 DELTA DUSTY PLUM 4000K CLO  
54893-402  
FAGERHULT



Installation Two point suspension c/c 48 mm. Connection For permanent connection with 230 V; built-in LED driver. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. Surface mounted mains cable possible 180°. Design Luminaire body in plastic lacquered in various colours. Supplied with 3 m wire, 2,2 m transparent cable and white, plastic ceiling cup. Height adjustment is done on the luminaire using a friction lock. The ceiling cup handles inclined ceilings up to 20°. Louvre Opal - opal acrylic diffuser. Delta – microprism louvre in acrylic (PMMA). Light distribution Delta Ø 450 – Direct/indirect 65/35. Opal Ø 450 – Direkt/indirekt 70/30. Dimming DALI/phase-pulse control as standard. Tunable White and e-Sense Tune on request.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27 W	CRI	80
Total flux	3041 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	35%
		Total power	27 W

## Mounting mode

Pendant

## Electric

System power: 27 W

## Shape and measurements

Length: 17.72 in

Width: 17.72 in

Height: 10.85 in

## Protection

IP: 20

## Adjustability

Fixed