

Product data sheet

I55-1500 LED 5400 GL 840
GLAMOX




IP
67

IK
10

Light source LED 5400 - 8100 lumen out Colour temperature 4000 K, CRI Ra 80, MacAdams 3 On request: 3000 K Driver Fixed output (HF) and DALI dimmable (1-100%). Driver life time up to 120.000 h/10 % (max failure) at Ta 25°C. Body material & colour Housing in Aluzink or acid-proof steel with white epoxy/polyester powder coated finish. Alternatively in unpainted acid-proof steel. Tempered 5 mm safety glass cover with silicone gasket, spring-loaded acid proof steel clips and safety wires. Mounting The luminaire is supplied with fixed end brackets. Accessories Suspension kits. Connection 5 pole 6 mm² screw terminal block. 5 x 2,5 mm² through wiring. 5-way chassis plug in both ends on request.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	41 W	CRI	80
Total flux	5511 lm	LOR	100%
Luminous efficacy	134 lm/W	ULOR	84%
		Total power	41 W

Mounting mode

Wall mounted

Electric

System power: 41 W

Shape and measurements

Length: 64.33 in

Width: 6.50 in

Height: 3.86 in

Protection

IP: 67

IK: 10

Adjustability

Fixed