

# Product data sheet


RICHARD V  
9.889.2152.00  
LEIPZIGER LEUCHTEN



IP  
55


Mounting height approx. 4.00 m - 5.00 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure sodium vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W    | LOR         | 59%     |
| Lamp flux          | 3500 lm | ULOR        | 15%     |
| Luminous efficacy  | 33 lm/W | Total flux  | 2071 lm |
| CCT                | 2000 K  | Total power | 62 W    |
| CRI                | 25      |             |         |



### 1 x High pressure sodium vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W    | LOR         | 59%     |
| Lamp flux          | 5600 lm | ULOR        | 15%     |
| Luminous efficacy  | 40 lm/W | Total flux  | 3313 lm |
| CCT                | 2000 K  | Total power | 83 W    |
| CRI                | 25      |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 24.21 in  
Diameter: 9.84 in

## Electric

System power: 62-83 W

## Protection

IP: 55