
Product data sheet


SYSTEM BATTEN LUMINAIRE TRAQ M600 15W 2150LM CRI > 80 3000K SILVER ON/OFF
2012.2949 - TRAQ INS M600 LED2150-830 WB SR ONF
REGENT



IP 20 IK 06

System batten luminaire Traq m600, for mounting on Traq Linear mounting rail, with LED, system power: 15 W, luminous flux of luminaire 2150 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 72'000 h, Photobiological safety: Safe., 230 V, direct light emission gear tray made of aluminium silver similar to RAL 9006 powder coated, with UV-resistant LED optics in polymethyl methacrylate (PMMA), wide beam, 1 integral control gear, ON/OFF, with halogen-free wiring, ENEC certified, support profile and system components to be ordered separately protection class I, ingress protection IP20, suitable for mounting on normally inflammable surfaces impact strength: IK 06, for ambient temperatures -10 to +45 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1249136 L = 595 mm, B = 65 mm, H = 10 mm

Light output 1



1 x LED

Nominal lamp power	16 W	LOR	100%
Lamp flux	2150 lm	ULOR	10%
Luminous efficacy	134 lm/W	Total flux	2150 lm
CCT	3000 K	Total power	15 W
CRI	80		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 2.56 in
Width: 23.43 in
Height: 0.79 in
Weight: 1.22 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 15 W
Appliance Class: I

Protection

IP: 20
IK: 06