


# Product data sheet

SNLED SERIES  
4SNLED-LD5-54HL-SLW-UNV-L935-CD1-U  
COOPER LIGHTING



Standard (SL) and High lumen/High Efficacy (HL) packages, High efficiencies - up to 153 LPW, Three different lens types for optical control, Two different reflectors for precise distribution control, Available CCT: 3000K, 3500K, 4000K and 5000K, Minimum CRI of 80; 90 CRI available, Class 2 driver with standard 0-10V dimming is NEMA 410 compliant, UL listed up to 40 C ambient temperatures, Step-dim, Fifth Light™ (DALI) and motion sensing options

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3500 K |
| Nominal lamp power | 43 W     | CRI         | 90     |
| Total flux         | 4369 lm  | LOR         | 100%   |
| Luminous efficacy  | 102 lm/W | ULOR        | 25%    |
|                    |          | Total power | 43 W   |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 4.00 in  
Width: 24.00 in  
Height: 1.50 in

## Adjustability

Fixed

## Electric

System power: 43 W  
Appliance Class: II

## Protection

IP: 47