## Product data sheet

PAR PENDANT (ORANGE) 8192141

ZERC








"Broberg & Ridderstråle asked themselves which was the best-loved light source of them all. The answer was Par 38, also known as press glass spot, which led to the pendant fitting Par. The designers wish to accentuate all the pleasant qualities of the light source. A warm, glare-free light with an attractive molten glass lens, which has been emphasized in the shape of the casing, covering both stand and lamp holder. So simple. So beautiful." Finish: Painted aluminium. Textile cable in matching colors. Incl. lightsource. Led information: 13W, light beam 25 degrees, 2700K. RA 80. Installation: Pendant, 2 m cable. Connection: Terminal block 2x2,25mm2, Design: Broberg & Ridderstråle 2012.

## Light output 1 (integrated)



| Lamp type          | LED     | CCT         | 2700 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 16 W    | CRI         | 80     |
| Total flux         | 1024 lm | LOR         | 100%   |
| Luminous efficacy  | 64 lm/W | Total power | 16 W   |

Mounting mode

Pendant

Shape and measurements

Length: 5.42 in Width: 5.42 in Height: 7.15 in

Adjustability

Fixed

Electric

System power: 16 W

Controller: Dimmable 1..10V

Protection

IP: 20

Designation labels: CE