# Product data sheet

GINO 2 WALL LUMINAIRES
GI-31621-VW-W40
LIGMAN

| IP 65 | IK 04 | ⏚ |

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

---

Light output 1 (integrated)

Lamp type	LED	CCT	4032 K
Nominal lamp power	5.6 W	CRI	80
Total flux	426 lm	LOR	100%
Luminous efficacy	76 lm/W	Total power	5.6 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.58 in
Width: 3.94 in
Height: 3.19 in
Weight: 1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 5.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 04
Surface temperature: 40°C