

# Product data sheet

SWEEP 500 DELTA LIGHT CORAL 3000K CLO  
54914-402  
FAGERHULT



Installation Two point suspension c/c 48 mm. Connection For permanent connection with 230 V; built-in LED driver. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. Surface mounted mains cable possible 180°. Design Luminaire body in plastic lacquered in various colours. Supplied with 3 m wire, 2,2 m transparent cable and white, plastic ceiling cup. Height adjustment is done on the luminaire using a friction lock. The ceiling cup handles inclined ceilings up to 20°. Louvre Opal - opal acrylic diffuser. Delta – microprism louvre in acrylic (PMMA). Light distribution Delta/Opal Ø 500 – Direct/indirect 55/45. Delta Ø 700 – Direct/indirect 60/40. Opal Ø 700 – Direkt/indirekt 65/35. Dimming DALI/phase-pulse control as standard. Tunable White and e-Sense Tune on request.

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 30 W     | CRI         | 80     |
| Total flux         | 3896 lm  | LOR         | 100%   |
| Luminous efficacy  | 130 lm/W | ULOR        | 47%    |
|                    |          | Total power | 30 W   |

## Mounting mode

Pendant

## Electric

System power: 30 W

## Shape and measurements

Length: 19.69 in

Width: 19.69 in

Height: 10.07 in

## Protection

IP: 20

## Adjustability

Fixed