


Product data sheet

OUTDOOR LIGHTING


V1-S1-90660-40D34-6603030 LEVANTE PLAZA 30W 3000K DALI

VARTON



LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: parking, squares and parks. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm). Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: YXJ11 Color rendering index: 70-79 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-plaza-dlya-ploshchadi/svetodiodnyy-svetilnik-varton-ulichnyy-levante-plaza-30-vt-kronshteyn-60mm-3000-k-ral9005-chernyy-mu/>

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	4100 lm	Total flux	4100 lm
Luminous efficacy	137 lm/W	Total power	30 W
CCT	3000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 23.46 in

Width: 5.35 in

Height: 3.98 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 66

IK: 03