Product data sheet

X-LINE PRO COMPACT 6000 PLX EDD 34 830 LINE / L-1690MM
19.4437.1413.34
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings using accessories. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 1690 x 60 x 72 mm. Weight 2,8 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 61,10%. Beam angle: (C0-C180) / (C90-C270) - 103,4° / 104,8°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 90000 h L80/B10. Luminaire luminous flux: 3922,6 lm. Power of luminaire: 37,8 W. Luminaire's light efficiency: 103,8 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	37.8 W	LOR	52%
Lamp flux	6420 lm	Total flux	3366 lm
Luminous efficacy	170 lm/W	Total power	37.8 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 66.54 in
Width: 2.36 in
Height: 2.83 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 37.8 W
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F