



Product data sheet

FLOODLIGHT VALUE SENSOR 10 W 4000 K IP44 BK
4058075268685
LEDVANCE



Floodlight with motion and daylight sensor. Product features: PIR motion detector and daylight sensor. Luminous efficacy: up to 90 lm/W. Symmetrical beam angle: 110° x 110°. Mounting bracket for up to 180° tilting. Type of protection: IP44. Impact resistance: IK06 (10 W to 50 W), IK08 (from 100 W). Ambient temperature in operation: -10...+40 °C. Product benefits: Demand optimized illumination due to flexible and programmable sensor. Semi-frosted, tempered glass cover for uniform illumination. Quick and simple installation thanks to low profile, compact and light weight design. Energy savings of up to 80 % compared to halogen lamp floodlights. 3 years guarantee. Areas of application: Replacement for floodlights with halogen lamps. Car parks and underpasses. Public areas. Building facades. Construction areas.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1000 W	CRI	80
Total flux	800 lm	LOR	100%
Luminous efficacy	1 lm/W	Total power	1000 W

Mounting mode

Wall mounted

Shape and measurements

Length: 606.30 in
Width: 366.14 in
Height: 248.03 in
Weight: 350 kg

Adjustability

Rotatable

Design

Material impression: Aluminum
Color of housing: Black

Electric

System power: 1000 W
Appliance Class: I

Protection

IP: 44
IK: 06
Designation labels: CE

Other operating numbers

Ambient temperature range: 14...104°F