Product data sheet

SINUS CURVED SEGMENT DI/ID BLACK PRISM. 45° R1440
P33-H54-9005E2840H3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40

high output LED 4000K CRI 90 54,6W 6309lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 13,1% https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.65 W	CRI	90
Total flux	1577 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	13.65 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.65 W	CRI	90
Total flux	1577 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	13.65 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.65 W	CRI	90
Total flux	1577 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	13.65 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.65 W	CRI	90
Total flux	1577 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	13.65 W

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 41.06 in
Width: 18.98 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 54.6 W

Protection

IP: 40