Product data sheet


TK2C RGBW L54 60° - BLUE
TANEK CORNICE RGBW
DEXTRA



IP 65 IK 10

Tanek Cornice RGBW - 1500mm, IP65, IK10 Cornice mounted colour change luminaire, constructed from robust 1.2mm CR4 steel, opal polycarbonate diffuser, weather resistant and salt spray tested, tamper resistant diffuser fixings, two 20mm side cable entries. DALI as standard with 4x DALI Addresses Options: LE3 - Lithium Emergency (390 lumen output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) RC - Reacta-Control Wireless Module WH - White Body BL - Black Body C83 - CRI 80, 3000K

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31.4 W	CRI	80
Total flux	4093 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	4%
		Total power	31.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.22 in
Width: 7.09 in
Height: 3.46 in

Adjustability

Fixed

Electric

System power: 31.4 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 10
Resistant to impact of balls
Designation labels: CE