


Product data sheet

SOLI - 66 NLT 952745 DIM5
27124 7235
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named SOLI - 66 NLT 952745 DIM5, available in the colour(s): black, white. This luminaire can be used with the following 48V lighting system(s): SOLISCAPE - PROFILE. This luminaire is equipped with LED array 21,1W / CRI>95 (R9: 96) / 2700K / 1925lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: reflector 45°.


Light output 1




1 x LED			
Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		



1 x LED			
Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		




1 x LED			
Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		



1 x LED

Nominal lamp power	21.1 W
Lamp flux	1925 lm
Luminous efficacy	91 lm/W
CCT	2700 K
CRI	95


LOR	73%
Total flux	1400 lm
Total power	24 W



1 x LED

Nominal lamp power	21.1 W
Lamp flux	1925 lm
Luminous efficacy	91 lm/W
CCT	2700 K
CRI	95


LOR	73%
Total flux	1400 lm
Total power	24 W



1 x LED

Nominal lamp power	21.1 W
Lamp flux	1925 lm
Luminous efficacy	91 lm/W
CCT	2700 K
CRI	95


LOR	73%
Total flux	1400 lm
Total power	24 W



1 x LED

Nominal lamp power	21.1 W
Lamp flux	1925 lm
Luminous efficacy	91 lm/W
CCT	2700 K
CRI	95


LOR	73%
Total flux	1400 lm
Total power	24 W



1 x LED


Nominal lamp power	21.1 W
Lamp flux	1925 lm
Luminous efficacy	91 lm/W
CCT	2700 K
CRI	95

LOR	73%
Total flux	1400 lm
Total power	24 W




1 x LED

Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		




1 x LED

Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		




1 x LED

Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		



1 x LED

Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		



1 x LED

Nominal lamp power	21.1 W	LOR	73%
Lamp flux	1925 lm	Total flux	1400 lm
Luminous efficacy	91 lm/W	Total power	24 W
CCT	2700 K		
CRI	95		

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 0.75 in
Width: 3.94 in
Height: 0.91 in

Electric

System power: 24 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE