


Product data sheet

TRET SKY 1 X 51.6W 360° 3000 K
GH8313.HLXT300EN
GHIDINI



Series of pole and bollards with indirect light available in various heights and configurations. Designed to illuminate squares, avenues, paths, parks, walkways and gardens without glaring with soft and omogeneous ligt distribution. With its strong steel base and the construction of the head in high oxidation resistant aluminum alloy which is subjected to nano-bonderite treatment and finished with texturized polyester powder paint, making the product resistant to atomospheric agents and UV rays, guaranteeing maximum protection over the years. The external screws are in stainless steel and on request also available in a vandal-proof version. The product is installed using pressure tie rods to be screwed directly into the ground or through tie rods embedded in the concrete. The product is equipped with the Ghidini water-lock system that prevents the rising of humidity from the power cable due to the alternating on and off cycles.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	90
Total flux	2615 lm	LOR	100%
Luminous efficacy	62 lm/W	ULOR	3%
		Total power	42 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 0.39 in

Diameter: 29.92 in

Adjustability

Fixed

Electric

System power: 42 W

Appliance Class: I

Protection

IP: 65