Product data sheet


HALO CENTRALIZED SUSPENSION DI/ID BLACK 1360MM
R48Z136-9005E2840L3S
PLANLICHT



IP 40


LED LO 4000K 91W 7257lm DALI https://katalog.planlicht.com/en-us/fam-halo/

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11.38 W	CRI	80
Total flux	907 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	50%
		Total power	11.38 W

Mounting mode

Pendant

Shape and measurements

Length: 53.54 in
Width: 53.54 in
Height: 2.44 in

Adjustability

Fixed

Electric

System power: 91 W

Protection

IP: 40
Designation labels: CE