# Product data sheet


INSPIRE PRISM 1500 BLACK 4200LM 4000K RA>80 PIR SENSOR
7021982128752
SG ARMATUREN



IP 20

Inspire Prism has a slim, modern design with powder-coated white or black outer surface. Direct light with prismatic, glare-free optics made of PMMA, combined with indirect light with a wide beam angle, gives an efficient light perfectly suited for offices and above desks. 2,5m cable and wireset for ceiling/T-profile fixing is included. Different control options are available; phase cut, pull-dim, Dali or SG Connect. If you want to position several luminaires in a row, the luminaires can easily be connected together with the supplied coupling piece or the flexible corner (accessory). Light distribution Direct/Indirect Light technic LED 34W 4000K Ra>80 SDCM 3 L90/B10 >100,000 hrs L96 >50,000 hrs Control/Dimming PIR Sensor Protection Class I IP20 Materials and finish Housing: Aluminium Optics: Polycarbonat (PC) Mounting/Connection Suspended, Indoor 2x2m wire kit Max. luminaires per circuit breaker: B10: 16, B16: 25, C10: 26, C16: 42

## Light output 1



### 1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 34 W | LOR | 100% |
| Lamp flux | 4200 lm | ULOR | 21% |
| Luminous efficacy | 124 lm/W | Total flux | 4201 lm |
| CCT | 4000 K | Total power | 34 W |
| CRI | 80 | | |

### Mounting mode

Pendant

### Shape and measurements

Length: 57.68 in
Width: 1.50 in
Height: 2.64 in

### Adjustability

Fixed

### Electric

System power: 34 W
Appliance Class: I

### Protection

IP: 20