Product data sheet

TX-MOVE
751145.004.1
RZB



IP 20 IK 04

Colour: silver, matt (approx. RAL 9006) Length: 570 mm Width: 119 mm Height: 65 mm Suspension length: 6000 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 41 W Rated luminous flux: 6300 lm Beam angle Down: 85° Luminous efficiency: 154 lm/W System power 2: 57 W Rated luminous flux 2: 8550 lm Luminous efficiency 2: 150 lm/W System power 3: 73 W Rated luminous flux 3: 10400 lm Luminous efficiency 3: 142 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1



1 x LED

Nominal lamp power	36.5 W	LOR	67%
Lamp flux	5200 lm	ULOR	14%
Luminous efficacy	95 lm/W	Total flux	3469 lm
CCT	4000 K	Total power	36.5 W
CRI	80		



1 x LED

Nominal lamp power	20.5 W	LOR	67%
Lamp flux	3150 lm	ULOR	14%
Luminous efficacy	103 lm/W	Total flux	2101 lm
CCT	4000 K	Total power	20.5 W
CRI	80		



1 x LED

Nominal lamp power	28.5 W	LOR	67%
Lamp flux	4275 lm	ULOR	14%
Luminous efficacy	100 lm/W	Total flux	2852 lm
CCT	4000 K	Total power	28.5 W
CRI	80		

Light output 2



1 x LED

Nominal lamp power	36.5 W	LOR	67%
Lamp flux	5200 lm	ULOR	14%
Luminous efficacy	95 lm/W	Total flux	3469 lm
CCT	4000 K	Total power	36.5 W
CRI	80		



1 x LED

Nominal lamp power	28.5 W	LOR	67%
Lamp flux	4275 lm	ULOR	14%
Luminous efficacy	100 lm/W	Total flux	2852 lm
CCT	4000 K	Total power	28.5 W
CRI	80		



1 x LED

Nominal lamp power	20.5 W	LOR	67%
Lamp flux	3150 lm	ULOR	14%
Luminous efficacy	103 lm/W	Total flux	2101 lm
CCT	4000 K	Total power	20.5 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 4.69 in
Width: 22.44 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 41-73 W

Protection

IP: 20
IK: 04