



Product data sheet

GATU 21-001W-20GHV/930, S
 21-001W-20GHV/930
 HALLA




21-001W-20GHV/930, S Luminaire recessed Material of luminaire: Colour of luminaire: Shape of luminaire: Angular Size: 350 x 185 x 100 mm
 Type of installation: Recessed Distribution: Direct Optics type: Reflector Protection class: II Voltage: 220-240V

Light output 1




1 x LED

Nominal lamp power	20.1 W	LOR	100%
Lamp flux	1950 lm	Total flux	1950 lm
Luminous efficacy	97 lm/W	Total power	20.1 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1790 lm	Total flux	1790 lm
Luminous efficacy	99 lm/W	Total power	18 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	15.9 W	LOR	100%
Lamp flux	1610 lm	Total flux	1610 lm
Luminous efficacy	101 lm/W	Total power	15.9 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	13.8 W	LOR	100%
Lamp flux	1440 lm	Total flux	1440 lm
Luminous efficacy	104 lm/W	Total power	13.8 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	11.8 W	LOR	100%
Lamp flux	1250 lm	Total flux	1250 lm
Luminous efficacy	106 lm/W	Total power	11.8 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	9.6 W	LOR	100%
Lamp flux	1050 lm	Total flux	1050 lm
Luminous efficacy	109 lm/W	Total power	9.6 W
CCT	3000 K		
CRI	90		



1 x LED


Nominal lamp power	22.2 W	LOR	100%
Lamp flux	2110 lm	Total flux	2110 lm
Luminous efficacy	95 lm/W	Total power	22.2 W
CCT	3000 K		
CRI	90		



1 x LED


Nominal lamp power	24.5 W	LOR	100%
Lamp flux	2260 lm	Total flux	2260 lm
Luminous efficacy	92 lm/W	Total power	24.5 W
CCT	3000 K		
CRI	90		

Light output 2




1 x LED

Nominal lamp power	20.1 W	LOR	100%
Lamp flux	1950 lm	Total flux	1950 lm
Luminous efficacy	97 lm/W	Total power	20.1 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	24.5 W	LOR	100%
Lamp flux	2260 lm	Total flux	2260 lm
Luminous efficacy	92 lm/W	Total power	24.5 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	22.2 W	LOR	100%
Lamp flux	2110 lm	Total flux	2110 lm
Luminous efficacy	95 lm/W	Total power	22.2 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1790 lm	Total flux	1790 lm
Luminous efficacy	99 lm/W	Total power	18 W
CCT	3000 K		
CRI	90		




1 x LED


Nominal lamp power	15.9 W	LOR	100%
Lamp flux	1610 lm	Total flux	1610 lm
Luminous efficacy	101 lm/W	Total power	15.9 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	13.8 W	LOR	100%
Lamp flux	1440 lm	Total flux	1440 lm
Luminous efficacy	104 lm/W	Total power	13.8 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	9.6 W	LOR	100%
Lamp flux	1050 lm	Total flux	1050 lm
Luminous efficacy	109 lm/W	Total power	9.6 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	11.8 W	LOR	100%
Lamp flux	1250 lm	Total flux	1250 lm
Luminous efficacy	106 lm/W	Total power	11.8 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 13.78 in

Width: 7.28 in

Height: 3.35 in

Adjustability

Tiltable

Electric

System power: 19.2-49 W

Appliance Class: II

Protection

IP: 20