

Product data sheet

DKN KREIS
10340.002
RZB




IP
40

IK
02

Series: DKN-Kreis, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: ~ 250 / 0 - 60 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 370, H 105 Lamp: 2 x E27 max. 75 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Beam Angle: 73°/65°/70°/71° Unified Glare Ratio: 18,6 EEC: A++ - E

Light output 1



2 x Compact fluorescent lamp

Nominal lamp power	15 W	Socket	E27
Lamp flux	850 lm	LOR	60%
Luminous efficacy	34 lm/W	ULOR	15%
CCT	2700 K	Total flux	1021 lm
CRI	80	Total power	30 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.13 in
Diameter: 14.57 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 40
IK: 02