


# Product data sheet

NADELSPOT PRO  
582089.0031.76  
RZB




IP  
65

IK  
07

Series: NADELSPOT PRO Wallscaping: elegant and innovative wall luminaire for accent lighting. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Cover made of ceramic-coated toughened glass with bayonet lock. COB LED with socket for easy replacement. Light emission: up. Spot lens, narrow beam. Light emission: down. with rotationally symmetrical reflector. Fixing on the wall outside the sealed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravalock System. Electrical plug and play featuring quick connector. Cable entry granting two cables for loop-through. Driver integrated. Dimmable DALI. Colour: anthracite metallic (DB703) Length: 100 mm Width: 154 mm Height: 127 mm Lamp: LED System power: 23 W Rated luminous flux: 1400 lm Luminous efficiency: 61 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 65

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	23 W	CRI	80
Total flux	1400 lm	LOR	100%
Luminous efficacy	61 lm/W	ULOR	13%
		Total power	23 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 6.06 in  
Width: 3.94 in  
Height: 5.00 in

## Adjustability

Fixed

## Electric

System power: 23 W

## Protection

IP: 65  
IK: 07