



Product data sheet

CHIP OVALE 30 GRILL A/EW 30W FBT WH-87 | FBT
005786_FBT
PERFORMANCE IN LIGHTING



Part number: 005786. Serie: CHIP. Wall, ceiling, bracket and post mounted luminaire for indoor and outdoor, comprising: Technopolymer housing, trim or screen. Pressed glass diffuser, internally coated. Class II. Aluminium reflector for E27 versions. Anti-ageing custom moulded silicone sealing gasket(s). Side entry for 20 mm conduits (drill out holes in housing arrangement). Anti-tampering screws available upon request. Product data | ETIM Group: EG000027. ETIM Class: EC002892. General information | Lampholder: E27. Luminaire wattage [W]: 1x30 W. IP degree of protection: IP55. IK06 1J xx3. Protection class: II. Optic: A/EW - . Net weight [kg]: 1.454. Overall length [mm]: 310. Overall width [mm]: 143. Overall height [mm]: 184. Mechanical features | Glow wire test [°C]: 750 °C. Electrical features | Installation | Application area: OUTDOOR. Mounting type: Wall / Ceiling surface. Min. ambient temperature [°C]: -30. Max. ambient temperature [°C]: 35. Side cable entry. Suitable for sea front installation. Light features | Lamps: 1. ILCOS: FBT. Certifications | CE certified. EAC certified. UKCA certified. RCM certified. Mountable on normally inflammable surfaces.

Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	22 W	LOR	90%
Lamp flux	1440 lm	Total flux	1296 lm
Luminous efficacy	65 lm/W	Total power	22 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 12.20 in
Width: 5.79 in
Height: 7.24 in

Adjustability

Fixed

Design

Material impression: Matt

Electric

System power: 22 W
Ballast: ECG
Appliance Class: I

Protection

IP: 55
IK: 06
Designation labels: CE

Other operating numbers

Ambient temperature range: 32...86°F