


Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, LENS WALLWASHER
AF2105108-33-40_36W
SCHMITZ | WILA



alphabet focus LED 4000 K Recessed Luminaire, Light distribution direct, asymmetric Wallwasher Lens Wallwasher Product: AF2105108-33-40 Operating technology: independent driver required Lens wall washer create a uniform illumination on vertical surfaces without any hard shadow. Room proportions can be perfectly emphasized thanks to a harmonious brightness distribution. Light Technique asymmetric light distribution highly precise optical system, combining primary focus lens and secondary light control lens CRI > 90 constant colour temperature 4000K chromaticity stability with <3SDCM lifetime 50.000 h (L70) aluminium reflector (Al99.98), high-polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2mm for homogeneous appearance in the ceiling frame colour white, RAL9016 Operating and assembly technology Order LED gear box separately Gear boxes suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 36 W Colour Rendering Index: 90 Colour Temperature: 4000 K Luminaire Luminous Flux: 2000 Lm System Efficiency: 51 Lm/W Number Luminaires LZ: 0.07 Connector: Screw Connector, 3 x 1.5 mm2 Reflector Size: Q15 Length: 177 mm Width: 177 mm Cut-out length: 170 mm Cut-out width: 170 mm Overhang OH: 145 mm Installation Depth RD: 200 mm Total Weight: 1.7 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF2105108-33-40_36W

Light output 1



1 x General service incandescent lamp

Nominal lamp power	39 W	LOR	100%
Lamp flux	2000 lm	Total flux	2000 lm
Luminous efficacy	51 lm/W	Total power	39 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.97 in
Width: 6.97 in
Height: 7.87 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 39 W
Appliance Class: II

Protection

IP: 20