


Product data sheet

NIKON 3 RECESSED EXTERIOR DOWNLIGHTS
NI-80521-M-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 200,000, 300,000 - Life time L80B10 Ta 50° 490,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - 6 mm thick front ring is available in stainless steel or aluminium - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Include control gear for NIKON 5, NIKON 6 - Remote driver is included for NIKON 1, NIKON 2, NIKON 3, NIKON 4 - Remote IP box is included for NIKON 1, NIKON 2, NIKON 3, NIKON 4

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	29.2 W	CRI	80
Total flux	3100 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	29.2 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.46 in
Diameter: 4.72 in
Weight: 0.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 29.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C