Product data sheet


X-LINE SLIGHT L-DOWN LED 4400 PLX EDD 04 840 / L-1134MM S-1,5M
19.4085.2623.04
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9005 (black). Dimensions: 1134 x 34 x 68 mm. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 75,50%. Beam angle: (C0-C180) / (C90-C270) - 99,6° / 103°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 3592,5 lm. Power of luminaire: 25,9 W. Luminaire's light efficiency: 138,7 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. There is the possibility of fitting a luminaire with a sound-absorbing housing.

Light output 1



1 x LED

Nominal lamp power	25.9 W	LOR	52%
Lamp flux	4790 lm	Total flux	2512 lm
Luminous efficacy	185 lm/W	Total power	25.9 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 44.65 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 25.9 W
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F