



Product data sheet

MINI MULTIPLE TRIMLESS FOR SMART KUP LED 3000K SPOT GE WHITE STRUC
12535109+12556209
MODULAR




Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your choice. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours. Connect Mini multiple with Smart by adding the Smart frontrings to your recessed spot.

Light output 1



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 6.2 W | LOR | 94% |
| Lamp flux | 550 lm | Total flux | 520 lm |
| Luminous efficacy | 84 lm/W | Total power | 6.2 W |
| CCT | 3000 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 9.2 W | LOR | 94% |
| Lamp flux | 739 lm | Total flux | 698 lm |
| Luminous efficacy | 76 lm/W | Total power | 9.2 W |
| CCT | 3000 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling recessed, Wall recessed

Shape and measurements

Length: 4.72 in
Width: 4.72 in
Height: 4.72 in
Weight: 0.69 kg

Adjustability

Free

Electric

System power: 6.2-9.2 W
Appliance Class: III

Protection

IP: 20
IK: 01