

Product data sheet

I60-1500 LED 4600 830 OP
GLAMOX




IP
44

IK
05

Light source i60-600: LED 2000 Lumen out i60-1200: LED 3600 / 4600 Lumen out i60-1500: LED 4600 / 6000 Lumen out Light source information: 3000 / 4000 K. CRI 80. CRI 90 and CCT on request. MacAdams 3. Ballast Fixed output (HF) and DALI dimmable. Body material & colour The luminaire housing is made of galvanized pre-painted steel with a second layer of white epoxy/polyester powder coated finish to achieve extra protection against corrosion. End caps in injection molded ASA. The diffuser is made of extruded opal fire rated polycarbonate. Mounting Ceiling or wall, on luminaire tracks or on horizontal wire. Can be used in evacuation shelters using a special evacuation shelter bracket. Accessories Suspension kits Connection 1 membrane gland in each end cap and 2 x membrane glands in top of luminaire housing. 5 pole 2,5 mm² push-in terminal block. 5 x 2,5 mm² through wiring on request. Integrated emergency light 1 or 3 hour emergency lighting (Standard, SelfTest or DALI addressable) except the for shortest version. Integrated sensors Can be supplied with ultra sonic movement sensor type U-SEN.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	4854 lm	LOR	100%
Luminous efficacy	135 lm/W	ULOR	84%
		Total power	36 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 59.13 in

Width: 6.50 in

Height: 2.24 in

Adjustability

Fixed

Electric

System power: 36 W

Protection

IP: 44

IK: 05