Product data sheet

DEECOS P MINI
911520.002_982672.002_982647.002
RZB

IP 20 IK 06

Series: DEECOS P mini Cylindrical pendant luminaire. Housing made of die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel, with magnetic attachment. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Oval light distribution for corridor. Best colour rendering index Ra>90. Transparent pendant cable 5 m, can be shortened, with integrated steel cable. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Suitable for accessory Deecos P Tube cylinder extensions 0.5 m, 0.75 m or 1 m. Colour: traffic white, matt (RAL 9016) Diameter: 87 mm Height: 195 mm Suspension length: 5000 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 90 System power: 20 W Rated luminous flux: 2000 lm Beam angle Down: 40° / 28° Luminous efficiency: 100 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	1110 lm	LOR	100%
Luminous efficacy	56 lm/W	ULOR	13%
		Total power	20 W

Mounting mode

Pendant

Shape and measurements

Height: 7.68 in
Diameter: 3.43 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 20 W

Protection

IP: 20
IK: 06